

# MENSE RUITER

## ORGELMAKER

DE PERSSTRAAT

55a

### KERKORGELS

MECHANISCH  
PNEUMATISCH  
STEMMEN  
ONDERHOUD  
REPAREREEN  
WINDMACHINES

### HARMONIUMS

Groningen,

nieuwly diameters Orgel H.K. Meppel.


Fluytprincif.

	C	c	ċ	ċ̇	ċ̇̇
Pr. 4.	86	48	20	10	13
H. 8.	105	57	36	24	19
Fl. 4	74	60	37	24	16
ƒ	(gesl. epl.)	(open epl.) →			
Cfamba 8 (nieuw)	-	46	29	19	12
Wondfluit 2' (conisch)	44 } 43 }	25 } 44 }	20 } 29 }	14 } 19 }	8 } 12 }
Quint 3	40	35	24	10	12
		gesl. epl.	open →		
Sax Quilten	{ 33 (1 1/2)	20	21 1/2 14 1/2	19 9	11 8
Fluit travers 8	-	-	36	25	17
Nim Col. 8 (nieuw).	-	43	26	17	11.
Dualc. 8	49	34	27	24	22.

Fluytprincif.  
H.D.

# MENSE RUITER ORGELMAKER

55a  
PETERSSTRAAT



**KERKORGELS**  
MECHANISCH  
PNEUMATISCH  
STEMMEN  
ONDERHOUD  
REPAREREEN  
WINDMACHINES  
**HARMONIUMS**

Wel Edel Gestr. Heer Mr. L. Haveman,  
O. Z. Achterburgwal 202-204,  
Amsterdam.

Groningen, 17-5-50

*Copieus*

Diameters Orgel H.K. Muffel.

Registers in volgorde van de lade  
Hoofdwerk.

	C	c	c̄	c̄	c̄
Prest. 8	125	83	40	30	18
B. 16	hout	97	82	44 <sup>s</sup>	26
H. 8	5275 hout	74	47	30	24 <sup>s</sup>
Tel. 4 (stems, orgel.)	90	65	30	25 <sup>s</sup>	17.
O. 4	83	46	30	16 <sup>s</sup>	11
Nasard 3 (corind)	72	boren = 1/2 Ø van boren.		19	- uitbreid.
O. 2	46	26	16 <sup>s</sup>	12	7.
Reinshijf 2 stuk.	46 (2st)	26	refut. 26	17	11
	32 (1 1/2)	20	20	13	8
Misc.	26	20	4/6'	13	9
3 stuk.	10 3/4	17	1/2'	10	7
	15 1/2	14	1/6'	13	9
Prest. 8	127	85	46	27 <sup>s</sup>	17.
T. 8	130	90	75	59	51